



## High quality homogeneous vinyl floorings suitable for a wide range of uses, from education and healthcare to offices and public buildings

### SENSORIAL BENEFITS

- Non directional patterns
- Practical and subtle designs

### FUNCTIONAL BENEFITS

- High wearing properties with wear class P
- Easy maintenance properties in most areas for lifetime; additional chemical treatment might be needed in hard wearing areas by time
- xr Pur reinforcement of surface

### ENVIRONMENTAL BENEFITS

- Recyclable
- Low maintenance regime saves cleaning chemicals and fresh water
- Low VOC emissions



Homogeneous vinyl flooring: requires only dry buffing to regenerate its original appearance throughout lifetime

**PRIMO PREMIUM  
MICRA PREMIUM  
ECLIPSE PREMIUM**

TECHNICAL DATA	STANDARDS	Primo Premium	Micra Premium	Eclipse Premium
<b>Classification</b>				
Classification	ISO 10581 (EN 649) commercial industrial	Classes: 34 43		
UPEC Classification	UPEC Classification	U4 P3 E2/3 C2	—	U4 P3 E2/E3 C2
	NF UPEC. certificate (NF 189)	312-017.1	—	312-021.1
<b>Characteristics</b>				
Total thickness	ISO 24346 (EN 428)	2.00mm		
Wear layer thickness	ISO 24340 (EN430)	3 000g/m <sup>2</sup>		
Surface treatment	-	PUR Reinforced		
Abrasion group	EN 660-2	Group P: ≤ 4.00mm <sup>3</sup>		
<b>Technical performances</b>				
Residual indentation	Average measured value	0.03mm		
	ISO 24343-1 (EN 433) requirement	≤ 0.10mm		
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>s1</sub> s1 ≥ 8 kW/m <sup>2</sup> Pass		
Dimensional stability	ISO 23999 (EN 434)	Rolls: ≤ 0.40% Tiles: ≤ 0.25%	≤ 0.40%	Rolls: ≤ 0.40% Tiles: ≤ 0.25%
Castor wheel test	ISO 4918 (EN 425)	Suitable		
Static electrical charge	EN 1815	< 2kV		
Light fastness	EN ISO 105-B02	≥ level 6		
Chemical resistance	ISO 846: Part C	Good resistance		
Fungi and bacteria resistance	ISO 26987 (EN 423)	Does not favour growth		
Clean room test	ASTM F51/00	Class A		
Slip resistance	DIN 51130 EN 13893	R9 ≥ 0.3		
Thermal resistance Underfloor heating	EN 12667 / DIN 52612	Approx. 0.01m <sup>2</sup> K/W Suitable - max. 27°C		
Form of delivery	ISO 24341 (EN 426) ISO 24342 (EN 427)	Sheet (rolls): 23lm x 2m Tiles (8 colours): 61 x 61cm	Sheet (rolls): 23lm x 2m	Sheet (rolls): 23lm x 2m Tiles: 61 x 61cm
Colours	EN 12667 / DIN 52612	16	30	22

The above information is subject to modifications for the benefit of further improvement (01/2014). For more detailed technical information, please contact Tarkett.



Download the product offer