

GRANIT SAFE.T



Homogeneous vinyl safety floorings for all applications

SENSORIAL BENEFITS

- Matching designs with Tarkett iQ Granit range
- Coordinated accessories for a perfect finish

FUNCTIONAL BENEFITS

- Exceptional and durable slip resistance properties (R10)
- Reinforced surfaces for easy maintenance
- Easy to install

ENVIRONMENTAL BENEFITS

- Unrivalled indoor air quality
- Improved carbon footprint



Homogeneous vinyl flooring with Safety Clean xp surface treatment: better slip resistance

GRANIT SAFE.T

TECHNICAL DATA	STANDARDS	Granit Safe.T
Classification		
Classification	ISO 10581 (EN 649) commercial industrial	Classes: 34 43
	UPEC Classification NF UPEC certificate number (Ref NF189)	U4 P3 E2/3 C2 312-023.1
Characteristics		
Wear layer thickness	ISO 24340 (EN 429)	2.00mm
Total thickness	ISO 24346 (EN 428)	2.00mm
Total weight	ISO 23997 (EN 430)	2 950g/m ²
Wear layer reinforcement	—	Safe.T Clean
Technical performances		
Residual indentation	Average measured value	0.02mm
	ISO 24343-1 (EN 433) requirement	≤ 0.10mm
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	B _{s1} ≥ 8kW/m ² Pass
Slip resistance	DIN 51130 EN 13893	R10 ≥ 0.3
Dimensional stability	ISO 23999 (EN 434)	≤ 0.40%
Castor chair test	ISO 4918 (EN 425)	Suitable
Chemical resistance	ISO 26987 (EN 423)	Good resistance
Fungi and bacteria resistance	DIN EN 846-A/C	Does not favour growth
Thermal resistance Underfloor heating	EN ISO 10456	0.01m ² K/W Suitable - Max 27°C
Light fastness	EN ISO 105-B02	≥ 6
Abrasion group Volume loss	EN 660-2	Group P: ≤ 4.00mm ³
Bare foot test	DIN 51097	Class B (≥ 18°)
Static electrical charge	EN 1815	< 2kV
Form of delivery	ISO 24341 (EN 426) ISO 24342 (EN 427)	Rolls: 25lm x 2m
Colours	—	16

The above information is subject to modifications for the benefit of further improvement (01/2014).
For more detailed technical information, please contact Tarkett.



Download the product offer