


Forbo FloorCare method

The Forbo Luxury Vinyl Tiles collection is easy to clean and maintain, thanks to its smooth and highly durable PUR coated surface.

Cleaning after installation




- Clean the floor with cleaner and a mop
- Pick up dirty water with a wiper and mop or a water vac
- Rinse with clean water and a mop
- Allow the floor to dry



- When intensive traffic is expected:
- Apply a full spray-film with an applicator
 - Buff the spray-film with a rotary machine and a buffing pad

Regular cleaning



- Wipe with a dust mop and dust cloth, or vacuum the floor



- Remove spots with a damp mop

Periodic cleaning



- Spray clean with a rotary machine and a buffing pad, use spray where necessary

Occasional maintenance



- Scrub with cleaner, a rotary machine and a scrub pad
- Pick up dirty water with a wiper and mop or a water vac
- Rinse with clean water and a mop
- Allow the floor to dry



- When intensive traffic is expected:
- Apply a full spray-film with an applicator
 - Buff the spray-film with a rotary machine and a buffing pad

Products

Forbo Cleaner is an effective and pH neutral cleaner.
Forbo Spray acts both as a spray cleaner and as a protective, satin gloss polish.
For more information: www.forbo-flooring.com.
If you want to use alternative products, please consult your local supplier.

Technical specifications

Allura meets the requirements of EN 649

		Allura Premium	Allura Ceramics	Allura 0.55	
	Total thickness	EN 428	2.5 mm	2.5 mm	2.2 mm
	Commercial use	EN 685	34 very heavy	34 very heavy	33 heavy
	Industrial use	EN 685	43 general	43 general	42 light general
	Collection size		95	12	50
	Wearlayer thickness	EN 429	0.7 mm	2.5 mm homogeneous	0.55 mm
	Tile size	EN 427	50x50 / 60x37.5 cm	61.5x61.5 cm	50x50 / 60x37.5 cm
	Plank size	EN 427	100x15 / 120x20 / 130x25 / 100x25 cm	-	100x15 / 120x20 cm
	Total weight	EN 430	ca 3600 g/m ²	ca 3200 / 4000g/m ²	ca 3150 g/m ²
	Packaging per carton tiles		3.0 m ² (12pcs) / 3.2 m ² (14 pcs)	4.2 m ² (11 pcs)	3.0 m ² (12 pcs) / 3.2 m ² (14 pcs)
	Packaging per carton planks		3.0 m ² (20 pcs) / 2.9 m ² (12 pcs) / 3.3 m ² (10 pcs) / 3.0 m ² (12 pcs)	-	3.0 m ² (20 pcs) / 2.9 m ² (12 pcs)
	Squareness and straightness	EN 427	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
	Abrasion resistance	EN 660	group T	group M	group T
	Slip resistance	DIN 51130	R10	R9	R10
	Acoustical impact noise reduction	EN ISO 717-2	6 dB	3 dB	5 dB
	Castor chair continuous use	EN 425	Superior	Superior	Very good
	Residual indentation	EN 433	≤ 0.04 mm	≤ 0.04 mm	≤ 0.04 mm
	Light fastness	ISO 105-B02	≥ 6	> 6	≥ 6
	VOC emissions	AgBB/DIBT	Suitable for indoor applications	Suitable for indoor applications	Suitable for indoor applications
	Resistance to chemicals	EN 423	Very good	Excellent	Very good
	Dimension stability (after exp. to heat)	EN 434	≤ 0.05%	≤ 0.05%	≤ 0.010%
	Heat insulation	EN 12664	0.0145 m ² K/W	0.011 m ² K/W	0.0122 m ² K/W
	Heat dissipation	DIN 52614	W1 36 KJ/m ² / W10 240 KJ/m ²	W1 35 KJ/m ² / W10 220 KJ/m ²	W1 44 KJ/m ² / W10 270 KJ/m ²
All Allura products meet the requirements of EN 14041					 EN 14041
	Reaction to fire	EN 13501	B _f -s1	B _f -s1	B _f -s1
	Slip resistance	EN 13893	DS - μ > 0.30	DS - μ > 0.30	DS - μ > 0.30
	Thermal conductivity	EN 12524	0.25 W/m ² K	0.24 W/m ² K	0.25 W/m ² K
	Body voltage	EN 1815	< 2 kV	< 2 kV	< 2 kV

The quality and environmental management system of Forbo Coevorden B.V. (NL) and Forbo Giubiasco S.A. (CH) where Forbo Allura is manufactured are certified in accordance with ISO 9001 and ISO 14001

